

RDA MD 4X4 CE - Fixed Base Model

RDA TMD 4X4 CE - Travelling Base Model

Medium Duty 4M x 4M

Column and Boom

Red-D-Arc's RDA MD 4X4 CE (fixed base model) and RDA TMD 4X4 CE (travelling base model) column and booms provide excellent welding results with maximum productivity through consistent and accurate placement of welding heads for automatic welding processes including inside, outside, longitudinal and circumferential welding applications and can also be used in conjunction with polishing and grinding heads. Structural steel with continuously welded roundways along with rack and pinion driven movement provide enhanced durability and extended overhaul intervals. Operated via push button pendant control providing 7 function boom control and 5 function travelling base control. Safety features include an integrated anti-fall device and UL /CE certified control boxes with IP65-rated enclosures. All Red-D-Arc column and booms have been tested and certified by UL to establish safe working loads - a first in the weld automation industry.



Specifications

Model	RDA MD 4X4 CE / RDA TMD 4X4 CE
Maximum Load	227 kg @ 457 mm C of G
Max. Height Under Boom	4000 mm / 4150 mm with travelling base
Vertical Boom Travel	3300 mm
Vertical Boom Speed	2000 mm/min
Lift Motor	0.75 kW with brake
Max. Horizontal Extension	4635 mm from CL of column
Horizontal Boom Travel	4000 mm
Horizontal Boom Speed	100 - 2000 mm/min
Boom Motor	0.37 kW
Rotation	Manual 360°, lockable
Control	Push button pendant, 15 m control cable
Control Functions	Up/down/in/stop/out/speed control/emergency stop
Primary Input Power	380 to 480 V, 3 phase, 50/60 Hz
Input Current at Rated Load	6.1 A
Overall Height	4950 mm / 5100 mm with travelling base
Weight	2700 kg / 3250 kg with travelling base
Control Box Ingress Protection Rating	IP65
Control Box Electrical Certification	UL508
Loading Capacity Certification	UL2011


RDA TMD 4X4 CE (Travelling Base Model)

Travelling Base Control	Uses column and boom push button pendant control
Control Functions	Forward/stop/reverse/speed control/emergency stop
Travel Speed	100 - 2000 mm/min
Rail Gauge	1500 CRS for 90 lb A.S.C.E. and A.R.A.-A rail

Red-D-Arc Welderentals rents and sells welding and weld-positioning equipment - around the world.



RDA MD 4X4 CE - Fixed Base Model
 RDA TMD 4X4 CE - Travelling Base Model

Medium Duty 4M x 4M
 Column and Boom




Fixed Base

Travelling Base



FIXED BASE MODEL

*150mm
 ADDITIONAL HEIGHT
 WITH TRAVELLING BASE



TRAVELLING BASE MODEL